

# Eagle Asphalt Short Track Special

## G-19 Eagle®

## G-24 Eagle®

- Tread design for responsive steering
- Consistent, repeatable performance for improved cost efficiency
- Compounds enhance tread life
- Stiff sidewall helps provide strength and toughness



G-19

G-24

Product Code	Size	Soft To Harder				Rec. Rim Width* (in.)	Overall Diameter (in.)	Circumf. (in.)	Section Width (in.)	Tread Width (in.)	Weight (lbs.)
--------------	------	----------------	--	--	--	-----------------------	------------------------	----------------	---------------------	-------------------	---------------

### Asphalt G-19

		A200	A300	A400	A500						
803-325-159 MATL. NO	23.5x9.5-13	2818 214911				9.0	23.5	74.0	12.0	9.5	15.0
803-240-159 MATL. NO	26.5x8.0-13			2672 208840		8.0	26.5	83.0	11.0	8.0	20.0
803-241-159 MATL. NO	27.0x8.0-15			2882 209161		8.0	27.0	85.0	11.0	8.0	20.0
803-251-159 MATL. NO	26.5x10.0-15			2772 212681		10.0	26.5	84.0	11.0	10.0	22.0
803-245-159 MATL. NO	27.0x10.0-15			2902 209898		10.0	27.0	86.0	13.0	10.0	23.0
803-247-159 MATL. NO	27.0x10.0-15				2925 213322	10.0	27.0	86.0	13.0	10.0	23.0

### Asphalt G-24

		A200	A300	A400							
803-407-159 MATL. NO	22.0x7.0-13			2714 208574		7.0	22.5	70.0	9.0	7.0	16.0
803-252-159 MATL. NO	23.0x7.0-13			2716 213412		7.0	23.0	72.0	9.0	7.0	16.5
803-893-159 MATL. NO	22.0x8.0-13		2832 208722			8.0	22.5	70.0	10.0	8.0	17.0
803-673-159 MATL. NO	23.0x8.0-13	2636 214382				8.0	23.0	72.0	11.0	8.0	17.0
803-675-159 MATL. NO	23.0x8.0-13		2833 209241			8.0	23.0	72.0	11.0	8.0	17.0
803-344-159 MATL. NO	27.0x7.0-15			2635 208616		6.0	26.5	84.0	9.0	6.0	15.0
803-235-159 MATL. NO	26.5x8.0-15		2862 208500			8.0	26.5	82.0	11.0	8.0	20.0
803-253-159 MATL. NO	26.5x8.0-15			2864 208671		8.0	26.5	82.0	11.0	8.0	20.0
803-232-159 MATL. NO	27.0x8.0-15		2863 208499			8.0	27.0	85.0	11.5	8.0	20.0
803-233-159 MATL. NO	27.0x8.0-15			2865 208331		8.0	27.0	85.0	11.5	8.0	20.0
803-256-159 MATL. NO	26.5x10.0-15		2677 208841			10.0	26.0	83.0	13.0	10.0	23.0
803-259-159 MATL. NO	27.0x10.0-15		2878 209152			10.0	27.0	85.0	13.0	10.0	24.0